

“DIRTY WATER” PRESSURE SWICHGAGE®

OPLFC Pressure SWICHGAGE® with Stainless Steel Diaphragm Assembly

The OPLFC-D is intended for applications where the liquid is mildly corrosive or contains semi-solids. Typical is “dirty water” (farmyard waste) pumping applications. It features the reliable OPLFC SWICHGAGE® and an improved stainless steel diaphragm assembly. All wetted parts are 316 stainless steel.

Ranges available:

0–100 psi / 0–7 bar
0–160 psi / 0–11 bar
0–200 psi / 0–14 bar
0–300 psi / 0–20 bar

Connection: 1 BSPT

How to Order:

Specify model and range.
Example: OPLFC-D-300

Available Extra:

Wall Mounting
Bracket MM 3264



Frank W. Murphy Ltd.
Swichgauge House,
Church Road,
Laverstock,
Salisbury SP1 1QZ
United Kingdom

Tel: 01722 410055
Fax: 01722 410088
Telex: 477088

Int. Tel: + 44 1722 410055
Int. Fax: + 44 1722 410088

Ligne directe pour service en Français
Tel: + 44 1722 410697
Fax: + 44 1722 410088



USA-ISO 9001 FM 28221
UK-ISO 9002 FM 29422

Frank W. Murphy PTE Ltd.
26 Siglap Drive
1545 Singapore
REPUBLIC OF SINGAPORE
Tel: (65) 241 3166 Fax: (65) 241 8382

Bureau de représentation en France
Tel: (33) 1 30 76 26 26 Fax: (33) 1 30 76 39 89